

SIP-based All-in-One IP PBXs with features to meet all your needs



Overview

The Zultys family of advanced Open Standards-based IP PBX products offer businesses of all sizes a feature-rich, energy-efficient path to IP telephony and Unified Communications services, with systems that do more in one box than any other IP PBX on the market. The energy-efficient MX250™ and MX30™ IP-PBX systems include a PSTN and SIP gateway right out of the box and are loaded with business-enhancing features such as Unified Communications, integrated Fax, Visual Voicemail, Contact Center features, Presence, Instant Messaging, **MXmobile™** for UC mobility, the integrated **MXconference™** audio conferencing feature and more. Zultys' IP PBXs may seamlessly link up to 128 offices and 10,000 employees into an enterprise-wide Unified Communications system.

Feature Rich Advanced IP PBX

The MX250 IP PBX is a feature-rich enterprise-class business IP telephony system that supports high quality VoIP and Unified Communications services for up to 250 users, while the MX30 IP PBX supports VoIP and Unified Communications for up to 30 users. Each comes with free SIP trunk support and a complete Unified Communications system. The IP PBXs also extend your Unified Communications to mobile phone users via the optional **MXmobile** feature.

All-in-One Servers Do Everything You Need

With the MX250 and MX30 IP PBXs, workers are unified across their organization into a single communication system – regardless of their location, even if they are on the road using their mobile phone. Users of the system may log in from any location and have full access to all system features while retaining their own personal user identity – whether they are logging in at the office, at home, while traveling, or from a different site.

Zultys IP phone systems combine the functions of an Internet gateway, with classic PBX functionality for high quality voice calling and Unified Communications across an organization. They provide powerful applications such as the Zultys **MXIE™** Unified Communications desktop client, presence, instant messaging, fax server, unified messaging, Find-me/Follow-me, advanced call handling, screen pops, and detailed call logs.

They integrate with Microsoft Exchange and also support contact center, ACD, IVR, video calls, text-to-speech announcements, call recording, and Visual Voicemail.

The systems are easily managed and maintained through the administrative console, referred to as **MXadministrator™**, an intuitive Graphical User Interface that can configure and monitor every aspect of the platform securely and remotely over LANs or WANs. You can configure and manage multiple systems at the same time from anywhere through one MXadministrator console.

Zultys' IP PBX systems are also highly energy and resource efficient. They provide a complete voice and Unified Communications solution in a single box for less energy than it takes to turn on a household light bulb.

Designed for SIP and Open Standards

The MX250 and MX30 IP PBXs were designed and built from the ground up as SIP Open Standards platforms to provide a complete IP telephony and Unified Communications solution. Most similar products typically use proprietary phones and have closed architectures since they were designed as a traditional PBX with a VoIP add-on, or as an IP core with telephony services added on later. Zultys not only provides its own line of high quality SIP desktop and wireless phones, but also supports a growing range of 3rd party phones and services. Zultys gives the user the freedom to tailor the deployment that's best for them.

Scale Seamlessly as Your Company's Needs Grow

Zultys' IP-PBXs seamlessly scale up to meet a company's growing communications needs, often without ever requiring more IP-PBXs. You can expand to meet your needs by upgrading user licenses (up to the service capacity of an IP PBX), or you can add additional IP PBXs. The Zultys **MXgroup™** feature enables multiple IP PBXs to be "grouped" in a peer-to-peer architecture to provide organization-wide Unified Communications across 128 different locations for up to 10,000 users. Our distributed platform enables survivability, high availability and disaster recovery over multiple locations.



Features	MX250	MX30
User Capacity	250 Users	30 Users
Expandable via MXcluster™	Yes – Up to 1000 Users	No
Free SIP trunk support	Yes	Yes
Maximum SIP trunks (can also be split with Analog + PCM)	60	10
Number of T1/E1 PSTN / ISDN interfaces	2 (up to 8 in a cluster)	1
Universal expansion slots for E1, T1, PRI ISDN, BRI ISDN, Analog FXO and Analog FXS interface cards	3	1
Complete IP PBX functionality	Yes	Yes
Hard-disk mirroring	RAID-1	No
Redundancy and Disaster Recovery	N+1	No
Integrated Battery Back-Up	Yes	No
Multiple Languages & Dialects	26	26
Support for Windows, Apple, Linux operating systems	Yes	Yes
Seamless Scalability via MXgroup™	5-10,000 users at 128 locations	5-10,000 users at 128 locations
Encryption & Security	DES, 3DES, AES	DES, 3DES, AES
Integrated Voicemail	400 hours	48 hours shared*
Fax Server: Termination, Origination & Storage	Yes	Yes
MXIE Unified Communications Client	Yes	Yes
Presence, Instant Messaging & Chat	Yes	Yes
MXconnect™ (use with any phone) and Softphone	Yes	Yes
Least-Cost Call Routing	Yes	Yes
Find Me/Follow Me & Twinning	17 destinations	17 destinations
Call Recording	166 hours	48 hours shared*
MXmobile™ Unified Communications option for mobile phones	Yes	Yes
Inbound Call Center/Contact Center support	Yes	Yes
Multiple ACDs, Hunt Groups and Operator Groups	64	8
Support for TAPI, SIP V.2, & VXML	Yes	Yes
MXconference™ integrated audio conferencing feature	Yes	Yes
Archiving for Regulatory Compliance	Yes	Yes
Multiple Automated Attendants	64	8
Call Detail Reports and Call Attached Data	Yes	Yes

MX250 PHYSICAL AND ENVIRONMENTAL

Operating temperature: 10°C to 40°C (50°F to 104°F)
 Storage temperature: 0°C to 50°C (32°F to 122°F)
 Weight: 8.2 kg (18 lb). Shipping weight 10.5 kg (23 lb)
 Size: 430 mm (W) x 269 mm (D) x 85 mm (H) (17" x 10½" x 3½")
 Power: 100/240 and 48V
 Mount: Standard 19" rack from front, mid, or rear; 2 RU (89 mm)
 Telecom and other compliance for global deployment

MX30 PHYSICAL AND ENVIRONMENTAL

Operating temperature: 10°C to 40°C (50°F to 104°F)
 Storage temperature: 0°C to 50°C (32°F to 122°F)
 Weight: 1.7 kg (3.7 lb). Shipping weight 2.2 kg (4.8 lb)
 Size: 210 mm (W) x 210 mm (D) x 50 mm (H) (8.3" x 8.3" x 2.0")
 Power: 90/264 and 5V
 Mount: wall or table
 Telecom and other compliance for global deployment

*MX30 provides 48 hours shared Voicemail & Call Recording. Zultys, Inc., the Zultys logo, the Zultys mark, MX250, MXIE and MXgroup are trademarks or registered trademarks of Zultys, Inc. All other trademarks used herein are the property of their respective owners. ©2010 Zultys, Inc. All rights reserved. Document Number 96-35003-01.